

BANKS BBQ

Combine Demolition Derby

Regulations

1. Pickup reel or bat reel removed.
2. Cutting bar removed.
3. Crop dividers removed.
4. Glass removed from Cabs.
5. Install seat belts.
6. Crash helmets required.
7. Original fuel tank removed (5 Gal. limit install in grain tank).
8. Rubber tires only, no fluid or foam in tires.
9. Straw choppers removed.
10. Header height 16-18 inches (fixed solid).
11. Unloading auger within 10 inches.
12. Rub bars can be placed around the radiator for protection.
13. Protection around variable speed acceptable.
14. All chains and belts removed that are not used for forward and reverse motion.
15. Disabled flag mounted 3 feet above grain tank.
16. For safety any number of iron pieces can be used.
17. Rear axle cannot be narrowed less than straw walkers unless factory option.
18. All combines need to be inspected and approved before entry by judges.
19. Hillside combines must be fixed solid.
20. Combines are only intended to last a 15-minute heat. Over reinforcement will only delay and lengthen the action, which will only lose the audience's interest. Reinforcement is subject to judges' decision, call and as if in doubt.
21. The drivers' area must have sufficient protection without limiting drivers' visibility.
22. Driver protection: An approved crash helmet, 2000 snell spec or newer with chin strap is required. Eye protection in the form of goggles or safety glasses is required for any helmet not having a fully functional face shield. A fire-retardant suit is highly recommended. At a minimum long pants and long sleeve shirts should be worn. Sturdy boots are recommended over tennis shoes or sneaker type footwear to provide foot and ankle protection.